

# DHI-TPC-M60 Thermal Monocular Camera



#### **Series Overview**

M60 captures sharp thermal imaging at a fast framerate for smooth, impeccable vision on running targets and from moving vehicles. Designed to increase situatonal awareness at any tme of day, M40 can detect humans, animals, and objects in complete darkness, haze, or through glaring light, equipping law enforcement professionals, hunters, and outdoor enthusiasts with reliable thermal imaging in tough conditons.

#### **Functions**

#### **Advanced Image Processing**

Designed to be precise, this thermal camera produces vivid video images through its enhanced detector and Dahua-developed image processing algorithm.

#### **Video Ranging**

With its hassle-free distance measurement feature, simply mark the top and bottom of a target on the screen, and the interface will automatically display the distance of the target from the monocular.

#### **Fire Detection**

Fire detection is now available for the first time with this monocular through Dahua's core technology. The monocular can automatically detect fires that break out in the scene and track them in real time.

#### Simultaneous Multi-user Connections

Multiple phones can connect to the monocular through the Wi-Fi at the same time. Through the mobile phone, you can watch the live view, capture images, record videos and configure parameters.

#### **Diopter Adjustment**

By using the diopter adjustment knob, the monocular can be set to match the eyesight of different users, ensuring that each user sees a clear image.

- Vanadium oxide uncooled focal plane detector.
- Ultra-low power consumption.
- Fire detection and alarm.
- · Connects to the mobile app through Wi-Fi.
- · Connects to the external display through the CVBS port.
- Provides a laser for aiming.
- · Calculates distance using video analysis.
- Lightweight and portable.
- IP67 rated.

#### Laser Eye Protection

The laser pointer is used to indicate a position. To protect the eyes from being injured, the laser pointer is automatically disabled after 10 s.

#### Portable and Low Power Consumption

With its small and lightweight design, it functions for longer periods while remaining fully charged, making long-term outdoor use more convenient.

#### Scene

Widely used in outdoor scenarios for hunting, rescue, animal observation, and more.

#### **Technical Specification**

General		
Appearance	Thermal Monocular Camera	
Туре	Monitor	
Thermal		
Detector Type	Vanadium oxide uncooled focal plane detector	
Effective Pixels	640 (H) × 512 (V)	
Pixel Pitch	12 μm	
Spectral Range	8 μm–14 μm	
Sensitivity (NETD)	≤35 mK@f/1.0	
Aperture	F1.0	
Focal Length	18 mm; 25 mm	
Field of View	18 mm (H: 24.0°; V: 19.4°) 25 mm (H: 18.0°; V: 13.5°)	
Focus Control	Fixed-focal	

## Outdoor Series | DHI-TPC-M60

Thermal Close Focus Distance		18 mm 15 m (49.21 ft) 25 mm 26 m (85.30 ft)	
Detection Range	18 mm	900 m (2,952.76 ft)	
	25 mm	1,240 m (4,068.24 ft)	
Thermal Digital Zoom		4 levels	
Color Palettes		4 (white hot; alarm; black hot; iron red)	
Display			
Video Compression		H.265	
Frame Rate		50 Hz	
Display Screen Dimensions		0.4 inch	
Resolution		1280 (H) × 960(V)	
Function			
Storage		Micro SD card (Max. 256 G)	
Laser Aiming		180 m (590.55 ft), Class 2 (IEC 60825-1)	
Buzzer		Yes	
Intelligen	ce		
Fire Detection		Yes	
Cold/Hot Spot Trace		Yes	
Port			
Analog Output		1 × CVBS output	
Wi-Fi Hotspo	ot	Yes	
USB		Micro USB	
Power			
Power Suppl	y	5 VDC, 0.5 A or built–in battery	
Battery Capa	city Display	Yes	
Power Consumption		<2.2 W	
Battery Life		>5 h (Wi-Fi hotspot off, @25°C)	
Charging Time		<3 h	
Environm	ent		
Operating Te	mperature	-20 °C to +55 °C (-4 °F to +131 °F)	
Operating Hu	umidity	≤90%	
Storage Tem	perature	-20 °C to +60 °C (-4 °F to +140 °F)	
Physical C	Physical Characteristics		
Protection		IP67	
Product Dimensions		187.5 mm × 66.5 mm × 68.5 mm (7.38" × 2.61" × 2.69") (L × W × H)	
Packaging Dimensions		228 mm × 186 mm × 124 mm (8.97" × 7.32" × 4.88") (L × W × H)	

Net Weight	450 g (0.99 lb)	
Gross Weight	1.1 kg (2.42 lb)	
Installation	Handheld; tripod	
Power Adapter	Included	
Lens	Included	
Bracket	Optional	
Drop Test Height	2 m (6.56 ft)	

## **Ordering Information**

Туре	Model	Description
Thermal Monocular Camera	DHI-TPC-M60-B18-Y	Lens: 18 mm; Color: Yellow
	DHI-TPC-M60-B25-Y	Lens: 25 mm; Color: Yellow
	DHI-TPC-M60-B18-G	Lens: 18 mm; Color: Black
	DHI-TPC-M60-B25-G	Lens: 25 mm; Color: Black

## Installation



### Dimensions (mm[inch])







Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.